AND 002. SPECIFICATION: NEW SECONDARY GLAZING - GLOSS WHITE FINISHED ALUMINIUM. UNITS TO BE FITTED WITH 4mm TOUGHENED GLASS. DIMENSIONS OF UNIT TO BE DETERMINED ON SITE AND CONFIRMED TO DISTRICT ARCHITECT PRIOR TO MANUFACTURE. SCREW FIXINGS INTO EXISTING TIMBER TO BE KEPT TO A MINIMUM. ALL WORKS TO BE CARRIED OUT IN ACCORDANCE WITH THE GUIDANCE GIVEN IN THE HISTORIC SCOTLAND PUBLICATIONS 'GUIDE FOR PRACTITIONERS 3 - CONSERVATION OF SASH & CASE WINDOWS' AND 'TECHNICAL ADVICE NOTE 3'. Softwood timber packer with DRAWING NOT TO SCALE. DIMENSION TO BE CHECKED half-round moulding. Moulding ON SITE. to match batten behind. Meeting rails of secondary glazing to be centred on sash & case meeting rails. OUTSIDE INSIDE New secondary glazing: fitted into window reveal Existing sash and roughly 200mm from existing case window. sash window. Softwood timber packer with half-round moulding. Moulding to match batten behind. Existing cill and wall linings. Raised platform required for access to upper windows in Function Room. Draghtstripping to ground floor windows. Existing sash and case window. Section A-A - Typical for windows **SMCP** WG7-WG12 and WF11-WF16 Edinburgh Castle (Scale 1:20) en Anne Building - Secondary Glazing Section A-A in Function Room HISTORIC
ENVIRONMENT
SCOTLAND
ARAINNEACHD
EACHDRAIDHEII
ALBA SCOTLAND 130P082016-SMC004 David Nicol 16th September 2016 SCALE 1:20

LOCATION OF SECTION A-A NOTED ON DRAWING 001